

- > Certified to the new UL1741/IEEE 1547
- > 10 yr. standard warranty
- > Prewired at factory
- > Integrated load-break rated AC/DC disconnect switch
- > Internet ready with Sunny WebBox
- > Improved CEC efficiency
- > Integrated fused series string combiner
- > Sealed electronics enclosure & Opticool
- > Ideal for commercial applications
- > Rugged stainless steel outdoor rated enclosure



Sunny Tower ST36 / ST42

The flexible solution for commercial PV systems

SMA brings you the best in commercial inverter solutions: The Sunny Tower. Designed with the installer in mind, we've combined ease of installation, lowest specific cost (\$/Watt), and the highest efficiency to maximize rebates and power production while minimizing your payback period. The Sunny Tower combines all the advantages of string inverters with the installation advantages of central inverters. The Sunny Tower offers you the flexibility and reliability you've come to expect from SMA.



Technical Data

Sunny Tower ST36 / ST42

	ST36	ST42
Input Data (DC)		
Max. Recommended Array Input Power (DC @ STC)	45.0 kW	52.5 kW
Max. DC Voltage	600 V	600 V
Peak Power Tracking Voltage	250 - 480 V @ 208 V 250 - 480 V @ 240 V	250 - 480 V @ 208 V 250 - 480 V @ 240 V
DC Max. Input Current	150 A	180 A
DC Voltage Ripple	< 5%	< 5%
Number of Fused String Inputs	24	24
PV Start Voltage (adjustable)	300 V	300 V
Output Data (AC)		
AC Nominal Power	36.0 kW	42.0 kW
AC Maximum Output Power	36.0 kW	42.0 kW
AC Maximum Output Current (per phase @ 208, 240, 277 V)	100 A, 87 A, 44 A	117 A, 101 A, 51 A
AC Nominal Voltage / Range	183 - 229 V @ 208 V 211 - 264 V @ 240 V	183 - 229 V @ 208 V 211 - 264 V @ 240 V
AC Frequency / Range	60 Hz / 59.3 Hz - 60.5 Hz	60 Hz / 59.3 Hz - 60.5 Hz
Power Factor	1	1
Efficiency		
Peak Inverter Efficiency	97.0 %	97.1 %
CEC weighted Efficiency	95.5 % @ 208 V, 240 V 96.0 % @ 277 V	95.5 % @ 208 V 96.0 % @ 240 V, 277 V
Mechanical Data		
Dimensions W x H x D in inches	43.3 x 70.5 x 39	43.3 x 70.5 x 39
Weight / With 6 Inverters / Total Shipping Weight in lbs.	330 / 1115 / 1700	330 / 1115 / 1700
Ambient temperature range	-13 to +113 °F	-13 to +113 °F
Power Consumption: standby / nighttime	< 42 W / 1.5 W	< 42 W / 1.5 W
Topology	PWM, true sinewave, current source	PWM, true sinewave, current source
Cooling Concept	Convection, regulated fan cooling	Convection, regulated fan cooling
Mounting Location Indoor / Outdoor (NEMA 3R)	● / ●	● / ●
Features		
LCD Display	●	●
Lid Color: aluminum / red / blue / yellow	● / ○ / ○ / ○	● / ○ / ○ / ○
Communication: RS485 / Wireless	○ / ○	○ / ○
Warranty: 10-year	●	●
Compliance: IEEE-929, IEEE-1547, UL 1741, UL 1998, FCC Part 15 A & B	●	●
Specifications for nominal conditions	● Included ○ Option – Not available	

Efficiency Curves

